

# ODC 288

---

## ODC 288

Eliminate Recalibration. Detect Any Material.

### Key Features

---

- **Zero recalibration** – sensor adapts automatically to any material (clear, opaque, metallic, nonwoven, mesh)
- **High resolution** – hardware resolution independent of sensing range
- **Material-agnostic detection** – fiber-optic technology based on light scattering and spatial filtering
- **Temperature immune** – unlike ultrasonic sensors, performance unaffected by temperature changes
- **One sensor, multiple applications** – edge guiding, width measurement, centerline detection, and more

### Benefits

---

- **Stop losing hours** to sensor recalibration when switching between materials
- **Eliminate changeover delays** – no manual sensor adjustments between product runs
- **End quality escapes** caused by undetected sensor drift between changeovers
- **Remove safety risks** from operators accessing sensors in awkward positions
- **Prevent hidden scrap** from temperature-related inaccuracies that plague ultrasonic sensors

## Specifications

---

<b>Sensor Type</b>	Fiber Optic (diffuse-reflective)	<b>Sensing Range</b>	288 mm (11.3 in)
<b>Resolution</b>	0.0635 mm (0.0025 in) or 0.127 mm (0.005 in)	<b>Repeatability</b>	>99.9%
<b>Linearity Error</b>	<0.25%	<b>Response Time</b>	20 ms standard, 5 ms with special firmware
<b>Camera Type</b>	CMOS line scan camera	<b>Light Source</b>	Infrared (880 nm), UV (385 nm), White light
<b>Working Distance</b>	15-25 mm (0.6-1 in)	<b>Cable Length</b>	Up to 10 m (33 ft)
<b>Connector</b>	M12 12-pin male A Coded	<b>Housing</b>	Aluminum Extrusion
<b>IP Rating</b>	IP54 (IP64 on request)	<b>Operating Temp</b>	-10°C to 65°C (14°F to 150°F)
<b>Controller Required</b>	Yes (SCU5 or SCU6x)	<b>Vacuum Compatible</b>	Yes

## Applications

---

- Edge sensing, measurement and guiding
- Centerline web position sensing, measurement and guiding
- Web width measurement and monitoring
- Thread/ribbon inspection
- Flag detection
- Registration mark detection
- Defect detection

## Available Configurations

---

Part Number	Configuration
3-410018	ODC 288-IR QD
3-410028	ODC 288-WL QD
3-410038	ODC 288-UV QD

Part Number	Configuration
3-411018	ODC 288-IR QD HR
3-411028	ODC 288-WL QD HR
3-411038	ODC 288-UV QD HR
7-020001	1" Mounting Bracket for WPS and ODC Sensors
7-020004	1.5" Mounting Bracket for WPS and ODC Sensors
7-020005	Mounting Bracket for 1" or 25 mm Extrusion for WPS, ODC and 1DC Sensors
7-020006	Mounting Bracket for 1.5" or 40 mm Extrusion for WPS, ODC and 1DC Sensors

## Supporting Documentation

---

### Manuals (3)

- ODC and WPS Installation for Center Guiding and Web Width Measurement
- Sensor Installation Recommendations: Inspection Applications
- WPS 112/221/440/900 or ODC 96/192/288/384/480/768/960 Sensor Installation for to Reduce the Effect of Twist

### 2D Drawings (2)

- New Mounting Brackets for WPS, ODC and 1DC sensors - 1.5 in or 40 mm extrusion
- New Mounting Brackets for WPS, ODC and 1DC sensors - 1in or 25 mm extrusion

### 3D Models (5)

- 1.5in Mounting Bracket for WPS and ODC Sensors
- 1in Mounting Bracket for WPS and ODC Sensors
- Mounting Bracket for 1.5in or 40mm Extrusion for WPS, ODC and 1DC Sensors
- Mounting Bracket for 1in or 25mm Extrusion for WPS, ODC and 1DC Sensors
- ODC 288-xx QD



Scan for datasheets, 3D models & full documentation  
<https://r2r.tech/products/odc-288>

### Ready to Get Started?

Contact our experts to discuss how this product fits your application.

**Phone:** +1 (888) 290-3215 | **Email:** experts@r2r.tech | **Web:** r2r.tech