

# 1DC 384

---

1DC 384: [rr sensor] with built-in controller with industrial ethernet output

One Sensor. Infinite Possibilities.

## Key Features

---

- **All-in-one design** – integrated sensor and controller eliminates external hardware, cables, and complexity
- **Zero recalibration** – sensor adapts automatically to any material (clear, opaque, metallic, nonwoven, mesh)
- **High resolution** – 0.0635 mm (0.0025 in) hardware resolution across the entire sensing width
- **Material-agnostic detection** – patented fiber-optic technology based on light scattering and spatial filtering
- **IP67 protection** – sealed aluminum housing withstands harsh industrial environments (IP68 available on request)
- **Native industrial Ethernet** – EtherNet/IP, PROFINET, EtherCAT, Modbus/TCP, CC-Link IE Field Basic
- **Vacuum compatible** – operates reliably in vacuum chamber applications

## Benefits

---

- **Stop paying for separate controllers** – all-in-one design eliminates external hardware and reduces total system cost
- **Eliminate integration complexity** – just power and one Ethernet cable replaces multi-component wiring
- **End unplanned downtime** from cable failures and connector issues between sensors and controllers
- **Stop losing hours** to sensor recalibration when switching between materials
- **Prevent hidden scrap** from temperature-related inaccuracies that plague ultrasonic sensors

## Specifications

---

<b>Sensor Type</b>	Fiber Optic (diffuse-reflective)	<b>Sensing Range</b>	384 mm (15.12 in)
<b>Hardware Resolution</b>	0.0635 mm (0.0025 in)	<b>Firmware Resolution</b>	Up to 0.015875 mm
<b>Repeatability</b>	>99.9%	<b>Linearity Error</b>	<0.25%
<b>Response Time</b>	20 ms standard (1 ms special)	<b>Camera Rate</b>	25 Hz - 1000 Hz
<b>Working Distance</b>	6-25 mm (0.25-1.0 in) optimal	<b>Max Edges</b>	128
<b>Light Source</b>	IR (880 nm), UV (385 nm), or White	<b>Camera Type</b>	CMOS line scan camera
<b>Input Voltage</b>	20-30 VDC	<b>Current Draw</b>	150-1500 mA
<b>Power Connector</b>	M8 4-pin male A-Coded	<b>Network Connector</b>	M8 4-pin female A-Coded
<b>Protocols</b>	EtherNet/IP, PROFINET, EtherCAT, Modbus/TCP, CC-Link IE Field Basic		
<b>Operating Temp</b>	-10°C to 65°C (14°F to 150°F)	<b>Protection Class</b>	IP67 (IP68 available on request)
<b>Housing Material</b>	Aluminum alloy (powder coated)	<b>Vacuum Compatible</b>	Yes
<b>Controller Required</b>	No (built-in)	<b>Interface</b>	Industrial Ethernet / APP / PLC

## Applications

---

- Web guiding (edge, center, and contrast guiding)
- Edge position measurement
- Multiple edge position measurement (up to 128 edges)
- Center position measurement
- Line/contrast position measurement
- Width measurement and coating width measurement
- Multiple strip width measurement
- Thread/string counting
- Flag detection and splice detection
- Tear detection and simple inspection

## Compatibility

---

### SUPPORTED LINE SPEEDS

1000+ fpm

### SUPPORTED MATERIAL TYPES

Nonwoven, Porous/Perforated

### SUPPORTED WEB WIDTHS

Medium (12"-48"), Wide (48"-72")

## Available Configurations

---

Part Number	Configuration
7-020005	Mounting Bracket for 1" or 25 mm Extrusion for WPS, ODC and 1DC Sensors
7-020006	Mounting Bracket for 1.5" or 40 mm Extrusion for WPS, ODC and 1DC Sensors
8-000012	1DC 384-IR EP
8-010012	1DC 384-IR PR
8-020012	1DC 384-IR MB
8-060012	1DC 384-IR EC

## Supporting Documentation

---

### Manuals (3)

- 1DC Series: Product Data Sheet
- Register Map for 1DC Series Roll-2-Roll® Sensor (v 4.3a+)
- Sensor Installation Recommendations: Inspection Applications

### 2D Drawings (3)

- 1DC 384-xx QD
- New Mounting Brackets for WPS, ODC and 1DC sensors - 1.5 in or 40 mm extrusion
- New Mounting Brackets for WPS, ODC and 1DC sensors - 1in or 25 mm extrusion

### 3D Models (3)

- 1DC 384
- Mounting Bracket for 1.5in or 40mm Extrusion for WPS, ODC and 1DC Sensors
- Mounting Bracket for 1in or 25mm Extrusion for WPS, ODC and 1DC Sensors

### Support Files (2)

- EtherNet/IP EDS File for Roll-2-Roll® Communication Module
- Rockwell/AB Add-on Instructions for 1DC Series of Roll-2-Roll® Sensor



Scan for datasheets, 3D models & full documentation

<https://r2r.tech/products/sensors/1dc-384>

### Ready to Get Started?

Contact our experts to discuss how this product fits your application.

**Phone:** +1 (888) 290-3215 | **Email:** [experts@r2r.tech](mailto:experts@r2r.tech) | **Web:** [r2r.tech](https://r2r.tech)